

IN THE CLAIMS:

1. – 24. (Cancelled).

25. (Previously Presented) An outside rear view mirror assembly (1) for a motor vehicle, said outside rear view mirror assembly (1) comprising:

a mirror housing (2) including a circumferential lateral wall (4) defining an opening (6), an insertion opening (7), and a back wall (5);

a mirror mounting bracket (3) fixedly securable to the motor vehicle and insertable into said mirror housing (2) through said insertion opening (7), said mirror mounting bracket (3) including a catch recess (17'); and

a snap-in tongue (15) defining a free end and extending out from said back wall (5) within said mirror housing (2) for positive locking engagement with said catch recess (12') of said mirror mounting bracket (3) when said mirror mounting bracket (3) is inserted into said mirror housing (2) to lock said mirror mounting bracket (3) therein such that said mirror housing (2) is fixedly secured to the motor vehicle.

26. (Cancelled)

27. (Previously Presented) An outside rear view mirror assembly (1) as set forth in claim 25 wherein said snap-in tongue (15) includes a catch piece (16) at said free end thereof to engage said catch recess (17').

28. (Previously Presented) An outside rear view mirror assembly (1) as set forth in claim 27 wherein said mirror mounting bracket (3) includes a positive locking component (13) extending out from said mirror mounting bracket (3) to guide said mirror mounting bracket (3) as it is inserted into said mirror housing (2).

Amendment

Application Filed: February 15, 2007

Serial No: 10/561,352

29. (Previously Presented) An outside rear view mirror assembly (1) as set forth in claim 28 wherein said back wall (5) of said mirror housing (2) includes an insertion tunnel (11) for receiving said positive locking component therein.

30. (Previously Presented) An outside rear view mirror assembly (1) as set forth in claim 29 wherein said positive locking component (13) includes a stop (24) for abutting said insertion tunnel (11) preventing said catch piece (16) from moving past said catch recess (17').

31. (Previously Presented) An outside rear view mirror assembly (1) as set forth in claim 30 wherein said catch recess (17') includes an angled surface (31) to abut and engage said catch piece (16).

32. (Previously Presented) An outside rear view mirror assembly (1) as set forth in claim 27 wherein said catch piece (16) extends laterally across said snap-in tongue (15).